



Enviro-Matt™ Bonded Fiber Matrix (BFM)

SDS Number: AKR002

Revision Date: 1/1/2017

Page 1 of 6

1 PRODUCT AND COMPANY IDENTIFICATION**Manufacturer**

PROFILE Products, LLC
750 LAKE COOK ROAD
SUITE 440
BUFFALO GROVE, IL 60089

Emergency: (800) 424-9300
Contact: ChemTrec Acct #: CCN792719
Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: Enviro-Matt™ Bonded Fiber Matrix (BFM)
Revision Date: 1/1/2017
SDS Number: AKR002
CAS Number: Not applicable
Product Use: Erosion control and revegetation mulch for hydraulic seeding.

Product Description: Green dyed wood fibers and a proprietary binder mixture.

2 HAZARDS IDENTIFICATION**Classification of the Substance or Mixture**

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):
None, None, None

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **NONE**

GHS Hazard Pictograms:

no GHS pictograms indicated for this product

GHS Hazard Statements:

H000 - None

GHS Precautionary Statements:

no GHS precautionary statements indicated

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Inhalation, skin contact, eye contact

Inhalation: Wood may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.

Skin Contact: Wood dust can cause irritation. Skin absorption is not known to occur.

Eye Contact: Wood dust can irritate the eyes.

Ingestion: No reports of human ingestion.

OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200


Enviro-Matt™ Bonded Fiber Matrix (BFM)

SDS Number: AKR002

Revision Date: 1/1/2017

Page 2 of 6

NFPA: Health = 1, Fire = 1, Reactivity = 0, Specific Hazard = n/a



3 COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
9000300	Proprietary	Guar Gum
0		Hydrocolloidal Based Polysaccharide Tackifier

4 FIRST AID MEASURES

- Inhalation:** Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.
- Skin Contact:** Usually not a problem. Wash off with running water if irritation is experienced.
- Eye Contact:** Open eyelids and flush with water.
- Ingestion:** Get medical attention.

5 FIRE FIGHTING MEASURES

- Flammability:** Combustible product
- Flash Point:** Not applicable
- Flash Point Method:** Not applicable
- Autoignition Temp:** 200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces
Flammable- Extinguish with water; same as a wood fire

6 ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7 HANDLING AND STORAGE

- Handling Precautions:** Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.
- Storage Requirements:** Store in a cool, dry place. Keep away from sources of ignition.



Enviro-Matt™ Bonded Fiber Matrix (BFM)

SDS Number: AKR002

Revision Date: 1/1/2017

Page 3 of 6

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling operations.
Personal Protective Equipment: Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.
Footwear: The product is slippery when wet. Wear appropriate footwear.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dyed green wood fibers - Pine & mixed hardwoods
Physical State: Wood Fibers Odor: Mild wood odor
Spec Grav./Density: Lighter than water
Vapor Pressure: N/A

10 STABILITY AND REACTIVITY

Chemical Stability: Stable product
Conditions to Avoid: Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).
Materials to Avoid: Strong acids and oxidizers
Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:
Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.
Occupational Exposure Limits:
Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m³ (Inhalable fraction); A4
Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust); 5 mg/m³ (Respirable fraction)
Irritancy: Wood dust is a mild irritant
Sensitization: Some wood dusts may cause allergic skin reactions



Enviro-Matt™ Bonded Fiber Matrix (BFM)

SDS Number: AKR002

Revision Date: 1/1/2017

Page 4 of 6

12

ECOLOGICAL INFORMATION

Guar Gum (CAS# 9000-30-0) is listed as an inert ingredient permitted for use in nonfood use pesticide products by EPA. It is also classified under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) as a minimal risk inert substance (List 4A) meaning that as a pesticide, Guar Gum is considered by the EPA to pose little or no risk to humans or the environment. The US Department of Agriculture (USDA) National Organic Program (NOP) also allows the use of Guar Gum in a variety of applications, but primarily as a pesticide in organic production operations. Finally, Guar Gum is listed on the Generally Recognized as Safe (GRAS) list by the Food and Drug Administration (FDA).

48-hr LC_{50} = >100% for *Daphnia magna* when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14

TRANSPORT INFORMATION



Enviro-Matt™ Bonded Fiber Matrix (BFM)

SDS Number: AKR002

Revision Date: 1/1/2017

Page 5 of 6

15	REGULATORY INFORMATION
----	-------------------------------

Component (CAS#) [%] - CODES

Guar Gum (9000300) [Proprietary] TSCA

Hydrocolloidal Based Polysaccharide Tackifier (0) [n/a%]

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act

COMPONENT / (CAS/PERC) / CODES

*Guar Gum / (9000300 n/a%) / TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List

NRC = Nationally Recognized Carcinogens

OSHAWAC = OSHA workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

EHS302 = Extremely Hazardous Substance

EPCRAWPC = EPCRA Water Priority Chemicals

HAP = Hazardous Air Pollutants

NJEHS = NJ Extraordinarily Hazardous Substances

NJHS = NJ Right-to-Know Hazardous Substances

OSHAPSM = OSHA Chemicals Requiring process safety management

SARA313 = SARA 313 Title III Toxic Chemicals

TSCA = Toxic Substances Control Act



Solutions for your Environment™

SDS

GHS Safety Data Sheet

PROFILE Products, LLC

Enviro-Matt™ Bonded Fiber Matrix (BFM)

SDS Number: AKR002

Revision Date: 1/1/2017

Page 6 of 6

16

OTHER INFORMATION

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).